PRIMO

UT5x8-16HSS *ABOVE*

UT5x10-16HSS
* RIGHT*

UT5x8-STN *ABOVE*

UT5x10-30HSS
SHOWN WITH
OPTIONAL SPARE
TIRE AND MOUNT
* RIGHT*

60" Wide Utility Models

STANDARD FEATURES

	UT5x8-STD	UT5x8-18HSS	UT5x8-26HSS	UT5x10-STN	UT5x10-18HSS	UT5x10-26HSS
Overall Width & Length	80"x146"	80"x146"	80"x146"	80"x170"	80"x170"	80"x170"
Deck Width & Length	60"x96"	60"x96"	60"x96"	60"x120"	60"x120"	60"x120"
Deck Height	18"	18"	18"	18"	18"	18"
Solid Height	N/A	16"	24"	N/A	16"	24"
Rail Height	12"	18"	26"	12"	18"	26"
GVRW	2000#	2000#	2000#	2000#	2000#	2000#
Weight	450#	475#	500#	500#	525#	550#
Payload	1550#	1525#	1500#	1500#	1475#	1450#
Torsion Axle	2000#	2000#	2000#	2000#	2000#	2000#
Wheels	15" Aluminum	15" Aluminum	15" Aluminum	15" Aluminum	15" Aluminum	15" Aluminum
Tires	ST205-75R15-C	ST205-75R15-C	ST205-75R15-C	ST205-75R15-C	ST205-75R15-C	ST205-75R15-C
Tie Downs	4 x 1200# 2 Per Side	4 x 1200# 2 Per Side	4 x 1200# 2 Per Side	4 x 1200# 2 Per Side	4 x 1200# 2 Per Side	4 x 1200# 2 Per Side
Tongue Frame	A-Frame 2" Coupler	A-Frame 2" Coupler	A-Frame 2" Coupler	A-Frame 2" Coupler	A-Frame 2" Coupler	A-Frame 2" Coupler
Swivel Jack	800# Capacity	800# Capacity	800# Capacity	800# Capacity	800# Capacity	800# Capacity
Bi-Fold Gate	60"x48"	60"x48"	60"x48"	60"x48"	60"x48"	60"x48"
Lighting	Ultra Bright LED	Ultra Bright LED	Ultra Bright LED	Ultra Bright LED	Ultra Bright LED	Ultra Bright LED