

PRIMO MODEL SPECIFICATIONS

Utility Trailers

| Model | Bed Width | Bed Length | Carrying Capacity | GVRW | Axle | No. of Axles | Tire Size | Trailer Weight |
|--------------|-----------|------------|-------------------|----------|---------------|--------------|---------------|----------------|
| UT5x8-STD | 60" | 96" | 1550 | 2000 lbs | 2000# Torsion | 1 | ST205-75R15-C | 450 |
| UT5x8-16HSS | 60" | 96" | 1525 | 2000 lbs | 2000# Torsion | 1 | ST205-75R15-C | 475 |
| UT5x8-30HSS | 60" | 96" | 1500 | 2000 lbs | 2000# Torsion | 1 | ST205-75R15-C | 500 |
| UT5x10-STD | 60" | 120" | 1500 | 2000 lbs | 2000# Torsion | 1 | ST205-75R15-C | 500 |
| UT5x10-16HSS | 60" | 120" | 1475 | 2000 lbs | 2000# Torsion | 1 | ST205-75R15-C | 525 |
| UT5x10-30HSS | 60" | 120" | 1450 | 2000 lbs | 2000# Torsion | 1 | ST205-75R15-C | 550 |
| UT6x10-STD | 72" | 120" | 2465 | 2990 lbs | 3500# Torsion | 1 | ST205-75R15-C | 525 |
| UT6x10-16HSS | 72" | 120" | 2440 | 2990 lbs | 3500# Torsion | 1 | ST205-75R15-C | 550 |
| UT6x10-30HSS | 72" | 120" | 2415 | 2990 lbs | 3500# Torsion | 1 | ST205-75R15-C | 575 |
| UT6x12-STD | 72" | 144" | 2390 | 2990 lbs | 3500# Torsion | 1 | ST205-75R15-C | 600 |
| UT6x12-16HSS | 72" | 144" | 2365 | 2990 lbs | 3500# Torsion | 1 | ST205-75R15-C | 625 |
| UT6x12-30HSS | 72" | 144" | 2340 | 2990 lbs | 3500# Torsion | 1 | ST205-75R15-C | 650 |
| UT82x12-LP | 82" | 144" | 2340 | 2990 lbs | 3500# Torsion | 1 | ST205-75R15-C | 650 |
| UT82x14-LP | 82" | 168" | 2290 | 2990 lbs | 3500# Torsion | 1 | ST205-75R15-C | 700 |

ATV Trailers

| Model | Bed Width | Bed Length | Carrying Capacity | GVRW | Axle | No. of Axles | Tire Size | Trailer Weight |
|--------------|-----------|------------|-------------------|----------|---------------|--------------|---------------|----------------|
| ATV82x12 | 82" | 144" | 2365 | 2990 lbs | 3500# Torsion | 1 | ST205-75R15-C | 625 |
| ATV82x12-ATP | 82" | 144" | 2315 | 2990 lbs | 3500# Torsion | 1 | ST205-75R15-C | 675 |
| ATV82x14 | 82" | 168" | 2315 | 2990 lbs | 3500# Torsion | 1 | ST205-75R15-C | 675 |
| ATV82x14-ATP | 82" | 168" | 2265 | 2990 lbs | 3500# Torsion | 1 | ST205-75R15-C | 725 |

Heavy Duty Utility Trailers

| Model | Bed Width | Bed Length | Carrying Capacity | GVRW | Axle | No. of Axles | Tire Size | Trailer Weight |
|-----------------|-----------|------------|-------------------|----------|------------------------|--------------|---------------|----------------|
| HUT82x16-TA-HSS | 82" | 192" | 5490 | 6990 lbs | 3500# Torsion (Brakes) | 2 | ST205-75R15-C | 1500 |
| HUT82x18-TA-HSS | 82" | 216" | 5390 | 6990 lbs | 3500# Torsion (Brakes) | 2 | ST205-75R15-C | 1600 |

Features:

Torsion Sure Lube Axle - Best suspension on the market - 5 year warranty from manufacturer

TIG Welded Frame Is Better Than MIG Welding - Less heat and cleaner welds - easy maintenance & prevents rust

Stainless Steel Hardware - Used wherever possible! Primo uses the most stainless steel fasteners of any aluminum utility trailer on the market.

Radial 15" Tires - Radials are proven to last longer and provide for a safer ride.

Aluminum Mag Wheels - Aluminum mags will not rust & look awesome!

All Recessed L.E.D Lights - Last longer & will not break as easy as standard lights especially when they are protected inside the frame.

Tubular A-Frame Tongue - Tongue is much stronger and allows wiring to be inside enclosed tube frame

Swing Up Roller Jack – makes it easy for you to maneuver your light weight trailer around the driveway and store when ready to travel.

Bi-Fold Gate – Lower profile gate for less wind resistance and allows for Kayak/Canoe carrying across the top of the trailer.

Stainless Steel ADJUSTABLE ramp clamp - Makes our PRIMO bi-fold ramp tight and secure so it does not rattle. Can be adjusted over the years to tighten.

Aluminum Extruded Decking Standard - Lighter and lasts virtually forever. Won't rot like wood will. Plus just looks a lot better.

PRIMO designed for the consumer – if you bend or dent a fender, side kit or ramp you can easily replace with simple tools (don't need to bring to welder).